



No Fault Sport Group, LLC
3112 Valley Creek Drive, Ste. C
Baton Rouge, LA 70808
225.215.7760 Phone / 225.291.3821 FAX

No Fault Safety Surface Maintenance Guidelines (Outdoors)

PLEASE READ INSTRUCTIONS BEFORE CLEANING

A. Routine Monthly Maintenance:

1. Broom, vacuum, blow, or hose off entire playground surface to remove loose debris such as sand, dirt, leaves, tree sap, chewing gum, bird droppings, scuff marks, etc. Pressure washer may be used, but must not exceed 1500 PSI and the spray nozzle cannot be placed closer than 12 inches to surface.
2. ISOLATED STAINS: On heavily stained isolated spots, while surface is still damp from hosing, apply a sufficient amount of full strength all purpose cleaner; using a hand-held spray bottle, scrub thoroughly with a 10" medium basine bristle scrub brush. Repeat as needed.
3. GENERAL AREA CLEANING: While surface is still damp from hosing, apply a mixture of full strength all purpose cleaner and water using a garden pump sprayer to a small area. Be sure to follow directions for use on the cleaner you choose from your local supplier. Use a 10" medium basine bristle scrub brush. Once the entire surface area has been cleaned, rinse thoroughly using a garden hose with a nozzle attachment.
4. WARNING: At no time can sharp objects (high heels, spikes, etc.), vehicles, or any excessive weight (over 1500 lbs) be allowed on the surface.

B. Helpful Hints:

1. Perform cleaning during early morning or late afternoon so that your cleaner will have time to react without evaporating.
2. Area to be cleaned must be slightly damp prior to applying cleansing solution.
3. Clean only a small areas at a time making sure it is thoroughly scrubbed to eliminate the possibility of dirty spots and/or streaking caused by areas missed while scrubbing.
4. It shall be at the owner's discretion whether to remove stains on a less than annual basis. The owner acknowledges that a stain may become more difficult or even impossible to remove if not addressed immediately.
5. This procedure provides no guarantee of stain removal.

C. Recommended Equipment & Supplies:

- | | |
|--|----------------------------------|
| √ Broom, Wet/Dry Shop Vac or Blower | √ Disposable rags |
| √ Garden hose with spray nozzle | √ Disposable gloves |
| √ One 1/2 gallon garden pump sprayer | √ Cleaning & rinsing buckets |
| √ Pressure washer recommended (1500 psi maximum) | √ 10" medium bristle scrub brush |
| √ JOMAX® House Cleaner and Mildew Killer (manufactured by Zinsser) | |
| √ All purpose cleaner in hand-held spray bottle, i.e. Formula 409™ | |

D. The followings chemicals may be detrimental to No Fault Safety Surface and should be avoided:

- | | |
|---|--------------------------|
| X Chlorine Bleach or other Disinfectants | X Ammonia |
| X Gasoline, Diesel, or hydraulic and lubricating oils | X Acids (including weak) |
| X Thinners, Mineral Spirits, Solvents (includes Organic Solvents) | |
| X Heavily concentrated degreasers (i.e. Grease Lightning and Simple Green) | |
| X NEVER USE A STEEL OR HARD PLASTIC BRUSH ON MANUAL OR ELECTRIC CLEANING UNITS. | |

Failure to read and follow instructions explicitly will result in damage to the surface and termination of the No Fault Safety Surface warranty.



No Fault Sport Group, LLC
3112 Valley Creek Drive, Ste. C
Baton Rouge, LA 70808
225.215.7760 Phone / 225.291.3821 FAX

No Fault Safety Surface Water Play System Additional guidelines for maintaining your water play area

- 1 No Fault Safety Surface Water Saturation System must have positive drainage. No standing water at any time.
- 2 For maximum results avoid chemical treatments such as Ozone or Bromine, as well as chlorine levels higher than 3ppm.
- 3 Foreign and excessive chemicals in the water will result in color fading, color bleeding and/or
- 4 No Fault recommends a water treatment system that is regulated and maintained daily.
- 5 A water treatment system where the water is recycled causing increased chemical content is not
- 6 The use of a potable water system is highly recommended.