

www.nofault.com

Introducing...

# NO FAULT Sport Floor

Call Toll-Free  
866-637-7678  
for a CD & samples

- Resilient and Durable
- Easy to install
  - 4' wide rolls*
  - 2' x 2' Zig Zag cut tiles*
- Stain Resistant
- Easy Maintenance
- Available in 1/4" or 5/16"



## Ideal Applications:

- ✓ Weight Rooms
- ✓ Offices/Work Areas
- ✓ Aerobic Areas
- ✓ Locker Rooms
- ✓ Cardiovascular Facilities
- ✓ Juice Bars
- ✓ Ice Skating Facilities
- ✓ Exposition Flooring




### Company Information:


No Fault Sport Group, LLC  
 3112 Valley Creek Drive Suite C  
 Baton Rouge, LA. 70808  
 Phone: 866-637-7678 (toll free)  
 Fax: 877-291-3821 (toll free)  
 Email: info@nofault.com

www.nofault.com


### Standard Colors:




Marble \*



Twilight \*  
Sky




Starlit  
Night



Terracotta  
Sky



Total \*  
Eclipse



Fiery  
Sky

\*colors available in 1/4" and zig-zag tiles



www.nofault.com

---

## No Fault Sport Floor (Sheet Roll) Specification and Data

### Physical Test Data

Tensile Strength  
Flexibility  
Static Dissipation  
Coefficient of Friction  
McBurney Indentation  
Thermal Conductivity  
Static Load Limit  
Chemical Resistance  
Impact Insulation Class  
Sound Transmission Coefficient  
Noise Reduction Coefficient  
Sustainability  
VOC Compliance

### ASTM

D 412  
F 137  
F 150  
D2047  
F142, 1,000 lbs.  
C518  
F970, 1,000lbs.  
F925  
E492  
E413  
C423  
E2129-01  
SOW-IAQ

### SBR Rubber

200 lb/in<sup>2</sup> min  
Pass 1/4" material  
10<sup>6</sup> to 10<sup>9</sup> ◦  
>0.6  
<0.120inches  
0.406 Btu-in/hr-ft<sup>2</sup>-°F  
<0.020in  
No Change  
45 dB minimum  
45 dB minimum  
0.10 sabin/ft<sup>2</sup>  
Data collected  
24 hr. 0.39 - 1 week 0.056

### Product Dimensions -- No Fault Sport Floor

#### Sheet Roll Width

48"  
48"

#### Thickness

6mm (1/4")  
8mm (5/16")

#### Weight (lbs/sq. ft)

1.25  
1.75

#### Zig Zag Tiles

2'x2'

8mm (5/16")

1.75

---

### Installation

Basic installation procedures and tools are the same as for other standard commercial resilient flooring and should be installed by an experienced floor cover mechanic certified by No Fault Sport Group.

---

### Adhesive

No Fault Sport Floor Adhesive is an easy to use, fast drying solution, for adhering No Fault Sport Flooring products to various substrates with moisture content up to 5.5 lbs. Only No Fault Sport Floor approved adhesive should be used. No Fault Sport Floor adhesive coverage is approximately 300 sq ft / 5 gal depending on substrate conditions and is available in 2-1/2 or 5 gallon containers.

---

### Warranty

No Fault Sport Flooring is guaranteed by No Fault Sport Group, LLC to be free from manufacturing defects on both material and workmanship. If such a defect is discovered, the customer must notify No Fault either through the contracting installer, distributor or directly. If found to be defective within one (1) year under normal non-abusive conditions, the sole remedy against the seller will be the replacement or repair of the defective goods. At seller's option, credit may be issued not exceeding the selling price of the defective goods.

---

No Fault Sport Group, LLC · 3112 Valley Creek Drive Suite C · Baton Rouge LA 70808

Phone: (225) 215-7760 Fax: (225) 291-3821

**www.nofault.com**